

Lavatrici verticali con parte superiore chiusa

Closed on top vertical washing and drying machines



CT 2300/500/4s

0,3 - 5 m/min	400 mm	2.300 mm	3 - 25 mm OPTIONAL 3 - 40 mm	19 *	7.690x2.200 xH3.380 mm	3.300 Kg	500 Kg OPTIONAL 800 Kg	4
12 - 197 "/min	15.7 "	90.5 "	1/8 - 1 " OPTIONAL 1/8 - 1.6 "		302.7x86.6 xH133.1 "	7,275 lbs	1,102 lbs OPTIONAL 1,764 lbs	

CT 2300/500/6s

0,3 - 5 m/min	400 mm	2.300 mm	3 - 25 mm OPTIONAL 3 - 40 mm	19 *	8.040x2.200 xH3.380 mm	3.700 Kg	500 Kg OPTIONAL 800 Kg	6
12 - 197 "/min	15.7 "	90.5 "	1/8 - 1 " OPTIONAL 1/8 - 1.6 "		316.5x86.6 xH133.1 "	8,157 lbs	1,102 lbs OPTIONAL 1,764 lbs	


CT 2600/500/4s

0,3 - 5 m/min	400 mm	2.600 mm	3 - 25 mm OPTIONAL 3 - 40 mm	19 *	7.690x2.200 xH3.680 mm	3.500 Kg	500 Kg OPTIONAL 800 Kg	4
12 - 197 "/min	15.7 "	102.3 "	1/8 - 1 " OPTIONAL 1/8 - 1.6 "		302.7x86.6 xH144.9 "	7,716 lbs	1,102 lbs OPTIONAL 1,764 lbs	

CT 2600/500/6s

0,3 - 5 m/min	400 mm	2.600 mm	3 - 25 mm OPTIONAL 3 - 40 mm	23 *	8.040x2.200 xH3.680 mm	4.000 Kg	500 Kg OPTIONAL 800 Kg	6
12 - 197 "/min	15.7 "	102.3 "	1/8 - 1 " OPTIONAL 1/8 - 1.6 "		316.5x86.6 xH144.9 "	8,818 lbs	1,102 lbs OPTIONAL 1,764 lbs	

* = standard (può variare in base ad eventuali optional inclusi) / standard (it may change according to the included options)



Vertikalen **Glaswaschmaschinen (oben geschlossen)**
 Máquinas **lavadoras** verticales **cerradas en el lado superior**
Laveuses verticales



	0,3 - 5 m/min	400 mm	3.000 mm	3 - 25 mm OPTIONAL 3 - 40 mm	23 *	8.610x2.200 xH4.080 mm	3.800 Kg	500 Kg OPTIONAL 800 Kg	4
CT 3000/500/4s	12 - 197 "/min	15.7 "	118.1 "	1/8 - 1 " OPTIONAL 1/8 - 1.6 "		338.9x86.6 xH160.6 "	8,377 lbs	1,102 lbs OPTIONAL 1,764 Kg	
CT 3000/500/6s	0,3 - 5 m/min	400 mm	3.000 mm	3 - 25 mm OPTIONAL 3 - 40 mm	23 *	8.960x2.200 xH4.080 mm	4.300 Kg	500 Kg OPTIONAL 800 Kg	6
	12 - 197 "/min	15.7 "	118.1 "	1/8 - 1 " OPTIONAL 1/8 - 1.6 "		352.8x86.6 xH160.6 "	9,479 lbs	1,102 lbs OPTIONAL 1,764 Kg	
CT 3300/500/4s	0,3 - 5 m/min	400 mm	3.300 mm	3 - 25 mm OPTIONAL 3 - 40 mm	23 *	8.610x2.200 xH4.380 mm	4.000 Kg	500 Kg OPTIONAL 800 Kg	4
	12 - 197 "/min	15.7 "	129.9 "	1/8 - 1 " OPTIONAL 1/8 - 1.6 "		338.9x86.6 xH172.4 "	8,818 lbs	1,102 lbs OPTIONAL 1,764 Kg	
CT 3300/500/6s	0,3 - 5 m/min	400 mm	3.300 mm	3 - 25 mm OPTIONAL 3 - 40 mm	23 *	8.960x2.200 xH4.380 mm	4.500 Kg	500 Kg OPTIONAL 800 Kg	6
	12 - 197 "/min	15.7 "	129.9 "	1/8 - 1 " OPTIONAL 1/8 - 1.6 "		338.9x86.6 xH172.4 "	9,920 lbs	1,102 lbs OPTIONAL 1,764 Kg	

* = standard (può variare in base ad eventuali optional inclusi) / standard (it may change according to the included options)