


Molatrici rettilinee elettroniche per l'esecuzione del **filo piatto con filetti** Electronic straight-line edging machines for the processing of **flat edge with arris**

Elektronischen Kantenbearbeitungsmaschinen zum automatischen Schleifen und Polieren der **flacher Kante mit Saum**

Canteadoras rectilíneas electrónicas para la ejecución de **canto plano con aristas**

Meuleuses rectilignes électroniques pour le façonnage du **joint plat avec arêtes**



| | | | | | | | | |
|--------------|-----------------------|------------------------------|----------------------------------------|----|---------------------------|-----------|------------------------------------------------------------|-----------|
| TL 10 | 0,3 - 5 m/min | H60 mm OPTIONAL H35 mm | 3 - 30 mm OPTIONAL 3 - 40 mm | 20 | 7.970x1.350 xH3.100 mm | 3.100 Kg | 800 Kg - 200 Kg/m OPTIONAL 1.000 Kg - 250 Kg/m | 1.600 Kg |
| | 12 - 197 "/min | H2.4 " OPTIONAL H1.4 " | 1/8 - 1.2 " OPTIONAL 1/8 - 1.6 " | | 313.8x53.1 xH122 " | 6,834 lbs | 1,764 lbs - 11.2 lbs/" OPTIONAL 2,205 lbs - 14 lbs/" | 3,527 lbs |
| | 10 9 8 7 6 5 4 3* 2 1 | | | | | | | |

| | | | | | | | | |
|----------------|-----------------------|------------------------------|----------------------------------------|----|---------------------------|-----------|------------------------------------------------------------|-----------|
| TL 10 c | 0,3 - 5 m/min | H60 mm OPTIONAL H35 mm | 3 - 30 mm OPTIONAL 3 - 40 mm | 21 | 7.970x1.350 xH3.100 mm | 3.100 Kg | 800 Kg - 200 Kg/m OPTIONAL 1.000 Kg - 250 Kg/m | 1.600 Kg |
| | 12 - 197 "/min | H2.4 " OPTIONAL H1.4 " | 1/8 - 1.2 " OPTIONAL 1/8 - 1.6 " | | 313.8x53.1 xH122 " | 6,834 lbs | 1,764 lbs - 11.2 lbs/" OPTIONAL 2,205 lbs - 14 lbs/" | 3,527 lbs |
| | 10 9 8 7 6 5 4 3* 2 1 | | | | | | | |

| | | | | | | | | |
|-----------------|-------------------------|--------|--------------------------------------------|----|---------------------------|-----------|------------------------------------------------------------|-----------|
| TL 10 dd | 0,3 - 5 m/min* | H60 mm | 3 - 30 mm** OPTIONAL 3 - 40 mm** | 20 | 8.315x1.350 xH3.100 mm | 3.600 Kg | 800 Kg - 200 Kg/m OPTIONAL 1.000 Kg - 250 Kg/m | 1.600 Kg |
| | 12 - 197 "/min* | H2.4 " | 1/8 - 1.2 *** OPTIONAL 1/8 - 1.6 *** | | 327.4x53.1 xH122 " | 7,936 lbs | 1,764 lbs - 11.2 lbs/" OPTIONAL 2,205 lbs - 14 lbs/" | 3,527 lbs |
| | 11 10 9 8 7 6 5 4 3 2 1 | | | | | | | |


| | | | | | | | | |
|--------------|--------------------------|------------------------------|----------------------------------------|----|---------------------------|-----------|------------------------------------------------------------|-----------|
| TL 11 | 0,3 - 5 m/min | H60 mm OPTIONAL H35 mm | 3 - 30 mm OPTIONAL 3 - 40 mm | 22 | 7.970x1.350 xH3.100 mm | 3.100 Kg | 800 Kg - 200 Kg/m OPTIONAL 1.000 Kg - 250 Kg/m | 1.600 Kg |
| | 12 - 197 "/min | H2.4 " OPTIONAL H1.4 " | 1/8 - 1.2 " OPTIONAL 1/8 - 1.6 " | | 313.8x53.1 xH122 " | 6,834 lbs | 1,764 lbs - 11.2 lbs/" OPTIONAL 2,205 lbs - 14 lbs/" | 3,527 lbs |
| | 11 10 9 8 7 6 5 4 3* 2 1 | | | | | | | |

| | | | | | | | | |
|----------------|--------------------------|------------------------------|----------------------------------------|----|---------------------------|-----------|------------------------------------------------------------|-----------|
| TL 11 c | 0,3 - 5 m/min | H60 mm OPTIONAL H35 mm | 3 - 30 mm OPTIONAL 3 - 40 mm | 22 | 8.315x1.350 xH3.100 mm | 3.600 Kg | 800 Kg - 200 Kg/m OPTIONAL 1.000 Kg - 250 Kg/m | 1.600 Kg |
| | 12 - 197 "/min | H2.4 " OPTIONAL H1.4 " | 1/8 - 1.2 " OPTIONAL 1/8 - 1.6 " | | 327.4x53.1 xH122 " | 7,936 lbs | 1,764 lbs - 11.2 lbs/" OPTIONAL 2,205 lbs - 14 lbs/" | 3,527 lbs |
| | 11 10 9 8 7 6 5 4 3* 2 1 | | | | | | | |



Molatrici rettilinee elettroniche ad **angolo variabile da 0 a 45°**
 Electronic straight-line edging machines with **variable angle from 0 up to 45°**

Elektronischen Kantenbearbeitungsmaschinen für normalen **Kanten und Gehrungsschliff von 0 bis 45 Grad**
 Canteadoras rectilíneas electrónicas para la ejecución de **ingletes con inclinaciones de 0 a 45°**
 Meuleuses rectilignes électroniques avec **angle variable de 0 à 45°**



TL 10 av

| | | | | | | | | | |
|----------------|------------------------------|--------------------------------|----------------------------------------|----|---------------------------|-----------|------------------------------------------------------------|-----------|---|
| 0,3 - 5 m/min | H85 mm OPTIONAL H60 mm | 0 - 45° OPTIONAL 0 - 60° | 3 - 30 mm OPTIONAL 3 - 40 mm | 21 | 8.315x1.350 xH3.100 mm | 3.800 Kg | 800 Kg - 200 Kg/m OPTIONAL 1.000 Kg - 250 Kg/m | 1.600 Kg | |
| 12 - 197 "/min | H3.3 " OPTIONAL H2.4 " | | 1/8 - 1.2 " OPTIONAL 1/8 - 1.6 " | | 327.4x53.1 xH122 " | 8,377 lbs | 1,764 lbs - 11.2 lbs/" OPTIONAL 2,205 lbs - 14 lbs/" | 3,527 lbs | |
| 10 | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| | | | | | | | | | |

TL 10 av c

| | | | | | | | | | |
|----------------|------------------------------|--------------------------------|----------------------------------------|----|---------------------------|-----------|------------------------------------------------------------|-----------|---|
| 0,3 - 5 m/min | H85 mm OPTIONAL H60 mm | 0 - 45° OPTIONAL 0 - 60° | 3 - 30 mm OPTIONAL 3 - 40 mm | 21 | 8.315x1.350 xH3.100 mm | 3.800 Kg | 800 Kg - 200 Kg/m OPTIONAL 1.000 Kg - 250 Kg/m | 1.600 Kg | |
| 12 - 197 "/min | H3.3 " OPTIONAL H2.4 " | | 1/8 - 1.2 " OPTIONAL 1/8 - 1.6 " | | 327.4x53.1 xH122 " | 8,377 lbs | 1,764 lbs - 11.2 lbs/" OPTIONAL 2,205 lbs - 14 lbs/" | 3,527 lbs | |
| 10 | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| | | | | | | | | | |